

Safety Data Sheet

1. Identification	
Product Information.	20800
Product Name:	Tuffcoat UT-200 Series Green
Recommended Use.	Paints
Uses advised against.	Read label instructions and SDS
Supplier.	Kop-Coat, Inc. / Kop-Coat Marine Group 36 Pine Street Rockaway, NJ 07866 1-800-221-4466
Emergency telephone number.	Chemtrec: +1-800-424-9300 USA Chemtrec: +1 703-527-3887 ex-USA 24 hrs./day, 7 days/week

2. Hazards Identification

GHS Classification in accordance with 29 CFR 1910.1200 Carcinogenicity, category 1B Flammable Liquid, category 4

GHS Pictograms



Signal Word Danger

Unknown Acute Toxicity

22.0% of the mixture consists of ingredient(s) of unknown acute toxicity

HAZARD STATEMENTS

Combustible liquid. May cause cancer.

Precautionary Statements - Prevention.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response.

If exposed or concerned: Get medical advice/attention. In case of fire: Use CO_2 dry chemical or foam to extinguish.

Precautionary Statements - Storage.

Store in a well-ventilated place. Keep cool. Store locked up.

Precautionary Statements - Disposal.

Dispose of contents in accordance with local/regional/national/international regulations.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>
Calcium carbonate (Limestone)	1317-65-3	10-25
Hydrotreated aliphatic petroleum distillates	64742-52-5	2.5-10
Diethylene glycol monoethyl ether	111-90-0	2.5-10
Titanium dioxide	13463-67-7	1.0-2.5
Zinc oxide	1314-13-2	0.1-1.0
Triethylamine	121-44-8	0.1-1.0
Talc	14807-96-6	0.1-1.0
Ethylene glycol	107-21-1	0.1-1.0
Ammonium hydroxide	1336-21-6	0.1-1.0

The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid Measures

Description of first-aid measures.

General advice.

Move victim to a safe isolated area. When symptoms persist or in all cases of doubt seek medical advice. Call a poison control center or doctor for treatment advice.

Inhalation.

Move to fresh air. Apply artificial respiration if victim is not breathing. Call a poison control center or doctor for treatment advice.

Skin contact.

Wash off immediately with soap and plenty of water. Remove all contaminated clothes and shoes. Remove and wash contaminated clothing before re-use. Call a poison control center or doctor for treatment advice.

Eye contact.

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Call a poison control center or doctor for treatment advice.

Ingestion.

Do not induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. If swallowed, call a poison control center or doctor immediately.

Symptoms.

See Section 2 and Section 11, Toxicological effects for description of potential symptoms.

Notes to physician.

Treat symptomatically.

5. Fire-fighting Measures

Extinguishing media.

Suitable extinguishing media.

Use:. Dry powder. Alcohol-resistant foam. Carbon dioxide (CO₂). Water may be used to cool and prevent the rupture of containers that are exposed to the heat from a fire.

Extinguishing media which shall not be used for safety reasons.

Water may be unsuitable for extinguishing fires.

Special hazards arising from the substance or mixture.

Vapors may travel to areas away from work site before igniting/flashing back to vapor source. Thermal decomposition can lead to release of irritating and toxic gases and vapors. Most vapors are heavier than air. Vapors may spread along ground and collect in low or confined areas (sewers, basements, tanks). Vapors may travel to source of ignition and flash back. Air/vapor mixtures may explode when ignited. Containers may explode when heated.

Advice for firefighters.

Evacuate personnel to safe areas.As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures.

Personal precautions.

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. All equipment used when handling the product must be grounded. Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Wear protective gloves/clothing and eye/face protection. Stop all work that requires a naked flame, stop all vehicles, stop all machines and equipment that may cause sparks or flames. Do not breathe vapors or spray mist. Avoid exceeding of the given occupational exposure limits (see section 8). Thoroughly decontaminate all protective equipment after use.

Advice for emergency responders.

Refer to protective measures listed in sections 7 and 8. Use personal protection recommended in Section 8.

Environmental precautions.

Prevent further leakage or spillage if safe to do so. Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. See Section 12 for additional Ecological information.

Methods and materials for containment and cleaning up.

Methods for Containment.

Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Prevent further leakage or spillage if safe to do so. Pick up and transfer to properly labeled containers. Clean contaminated surface thoroughly. Ground and bond containers when transferring material. Take precautionary measures against static discharges. Use personal protective equipment. Remove all sources of ignition.

Methods for cleaning up.

Prevent further leakage or spillage if safe to do so. Keep away from open flames, hot surfaces and sources of ignition. Keep in suitable and closed containers for disposal. All equipment used when handling the product must be grounded. Keep combustibles (wood, paper, oil, etc) away from spilled material. Ventilate the area. Use personal protective equipment as required. Shut off ignition sources; including electrical equipment and flames. Clean contaminated objects and areas thoroughly while observing environmental regulations. Never return spills in original containers for re-use.

Reference to other sections.

See section 8 for more information.

7. Handling and Storage

Conditions for safe storage, including any incompatibilities.

Advice on safe handling.

Avoid contact with skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Wash hands before breaks and immediately after handling the product. All equipment used when handling the product must be grounded. Take precautionary measures against static discharges. Do not breathe vapors or spray mist. Use according to package label instructions. Ground and bond containers when transferring material.

Hygiene measures.

Handle in accordance with good industrial hygiene and safety practice for diagnostics. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Storage Conditions.

Keep container closed when not in use. Keep in properly labeled containers. Keep containers tightly closed in a dry, cool and well-ventilated place. Store in accordance with local regulations. Keep from freezing. Keep away from food, drink and animal feedingstuffs. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits				
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
Calcium carbonate (Limestone) Titanium dioxide	N.E. 10 mg/m ³	N.E. N.E.	15 mg/m ³ 15 mg/m ³	N.E. N.E.

Zinc oxide	2 mg/m ³	10 mg/m ³	5 mg/m ³	N.E.
Triethylamine	0.5 ppm	1 ppm	25 ppm	N.E.
Talc	2 mg/m ³	N.E.	N.E.	N.E.
Ethylene glycol	25 ppm	50 ppm	N.E.	N.E.

TLV = Threshold Limit Value TWA = Time Weighted Average PEL = Permissible Exposure Limit STEL = Short-Term Exposure Limit N.E. = Not Established

Engineering Measures.

Ensure adequate ventilation, especially in confined areas. Apply technical measures to comply with the occupational exposure limits.

Personal protective equipment.

Eye/Face Protection.

If splashes are likely to occur, wear:. Face-shield. Safety glasses with side-shields. Tightly fitting safety goggles.

Skin and body protection.

Use:. Long sleeved clothing. Protective shoes or boots. Solvent-resistant gloves. Solvent-resistant apron and boots. Wear impervious gloves and/or clothing if needed to prevent contact with the material. Gloves must be inspected prior to use. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Remove and wash contaminated clothing before re-use.

Respiratory protection.

In case of inadequate ventilation wear respiratory protection. If exposure limits are exceeded or irritation is experienced, respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

9. Physical and chemical properties.

Information on basic physical and chemical properties.

Physical state	 Liquid
Appearance	No Information
Color	Green
Odor	No Information
Odor Threshold	No Information
рН	No Information
Melting/freezing point., °C (°F)	No Information
Flash Point., °C (°F)	91 (195.80)
Boiling point/boiling range., °C (°F)	100 - 3,000 (212 - 5432)
Evaporation rate	No Information
Explosive properties.	No Information
Vapor pressure.	No Information
Vapor density.	No Information
Specific Gravity. (g/cm ³)	1.197
Water solubility.	No Information
Partition coefficient.	No Information
Autoignition temperature.,°C	No Information
Decomposition Temperature °C.	No Information
Viscosity, kinematic.	> 22mm2/s
Other information.	
Volatile organic compounds (VOC) content.	53 g/l
Density, lb/gal	9.970
· •	

10. Stability and Reactivity

Reactivity.

Stable under normal conditions.

Chemical stability.

Stable under recommended storage conditions.

Possibility of hazardous reactions.

None known based on information supplied.

Conditions to Avoid.

Heat (temperatures above flash point), sparks, ignition points, flames, static electricity. Keep away from heat and sources of ignition. Do not freeze.

Incompatible Materials.

None known based on information supplied.

Hazardous Decomposition Products.

Thermal decomposition can lead to release of irritating gases and vapours. Possible formation of carbon oxides, nitrogen oxides, and hazardous organic compounds.

11. Toxicological Information

Information on toxicological effects.

Acute toxicity.

Product Information

No Information

The following values are calculated based on chapter 3.1 of the GHS document.

ATEmix (oral)	76,569.5 mg/kg
ATEmix (dermal)	76,569.5 mg/kg

Component Information.

CAS-No. Chemi	ical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
64742-52-5 Hydrotr	reated aliphatic petroleum distillates	5000	5000	N.I.
111-90-0 Diethyle	lene glycol monoethyl ether	10502 mg/kg Rat	N.I.	N.I.
1314-13-2 Zinc ox	kide	>5000 mg/kg Rat	N.I.	>5.7 mg/L Rat (Dust)
121-44-8 Triethyl	lamine	460 mg/kg Rat	415 mg/kg Rabbit	14.5 mg/L Rat (Vapor)
107-21-1 Ethylen	ne glycol	2000 mg/kg (Rat)	10600 mg/kg Rat	N.I.
1336-21-6 Ammor	nium hydroxide	350 mg/kg Rat	N.I.	N.I.
N.I. = No Information				
Skin corrosion/irritation.				
SKIN IRRITANT.				
Eye damage/irritation	<u>).</u>			
No Information				
Respiratory or skin se	ensitization.			

No Information

Ingestion.

May be harmful if swallowed.

Germ cell mutagenicity.

No Information

Carcinogenicity.

No Information

No Information

CAS-No.	Chemical Name	IARC	<u>NTP</u>	<u>OSHA</u>
13463-67-7	Titanium dioxide	IARC Group 2B	-	-
14807-96-6	Talc	IARC Group 3	-	-
Reproductive toxicity.				

Specific target organ systemic toxicity (single exposure).

No Information

Specific target organ systemic toxicity (repeated exposure).

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard.

No Information

Primary Route(s) of Entry

No Information

12. Ecological Information

Toxicity.

14.54% of the mixture consists of ingredient(s) of unknown aquatic toxicity

Ecotoxicity effects.

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to daphnia and other aquatic invertebrates
Hydrotreated aliphatic petroleum distillates 64742-52-5	-	LC50 96 h Oncorhynchus mykiss >5000 mg/L	EC50 48 h Daphnia magna >1000 mg/L
Diethylene glycol monoethyl ether 111-90-0	-	LC50 96 h Lepomis macrochirus 10000 mg/L, LC50 96 h Lepomis macrochirus 19100 - 23900 mg/ L, LC50 96 h Oncorhynchus mykiss 11400 - 15700 mg/L, LC50 96 h Pimephales promelas 11600 - 16700 mg/L	
Zinc oxide 1314-13-2	-	LC50 96 h Danio rerio 1.55 mg/L	-
Triethylamine 121-44-8	-	LC50 96 h Pimephales promelas 43.7 mg/L	EC50 48 h Daphnia magna 200 mg/L
Talc 14807-96-6	-	LC50 96 h Brachydanio rerio >100 g/L	-
Ethylene glycol 107-21-1	EC50 96 h Pseudokirchneriella subcapitata 6500 - 13000 mg/L	LC50 96 h Oncorhynchus mykiss 41000 mg/L, LC50 96 h Oncorhynchus mykiss 14 - 18 mL/L, LC50 96 h Lepomis macrochirus 27540 mg/L, LC50 96 h Oncorhynchus mykiss 40761 mg/L, LC50 96 h Pimephales promelas 40000 - 60000 mg/L, LC50 96 h Poecilia reticulata 16000 mg/L	EC50 48 h Daphnia magna 46300 mg/L
Ammonium hydroxide 1336-21-6	-	LC50 96 h Pimephales promelas 8.2 mg/L	EC50 48 h water flea 0.66 mg/L, EC50 48 h Daphnia pulex 0.66 mg/L

Persistence and degradability.

No data are available on the product itself.

Bioaccumulative potential.

Discharge into the environment must be avoided.

CAS-No.	Chemical Name	log POW
111-90-0	Diethylene glycol monoethyl ether	-0.8
121-44-8	Triethylamine	1.45
107-21-1	Ethylene glycol	-1.93

Mobility in soil.

No information

Other adverse effects.

No information

13. Disposal Considerations

Waste Disposal Guidance.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

DOT

Shipping Name:	Combustible Liquid, n.o.s
Hazard Class:	Comb liq.
UN/NA Number:	NA1993
Packing Group:	III
Additional Information:	LTD QTY: This product may be reclassified as "limited quantity" per 49 CFR 173.150 (b)(3)
IMDG	No Information
Additional Information:	Not regulated
IATA	No Information
Additional Information:	Not regulated

15. Regulatory Information

International Inventories:

TSCA	Complies
DSL	-
DSL/NDSL	-
EINECS/ELINCS	-
ENCS	-
IECSC	-
KECI	-
PICCS	-
AICS	-
NZIoC	-
TCSI	
TSCA	United States Toxic Substances Control Act Section 8(b) Inventory.
DSL	Canadian Domestic Substances List.
DSL/NDSL	Canadian Domestic Substances List/Canadian Non-Domestic Substances List
EINECS/ELINCS	European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances.
ENCS	Japan Existing and New Chemical Substances.
IECSC	China Inventory of Existing Chemical Substances.
KECL	Korean Existing and Evaluated Chemical Substances.
PICCS	Philippines Inventory of Chemicals and Chemical Substances.
AICS	Australian Inventory of Chemical Substances.
NZIoC	New Zealand Inventory of Chemicals.
TCSI	Taiwan Chemical Substance Inventory

U.S. Federal Regulations:

SARA SECTION 313:

This product does not contain any chemicals that are subject to the reporting requirements of SARA 313. **TOXIC SUBSTANCES CONTROL ACT 12(b):**

This product does not contain any chemicals that are subject to the reporting requirements of TSCA 12(b).

CALIFORNIA PROPOSITION 65 CARCINOGENS

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:.

Chemical Name	CAS-No.	
Titanium dioxide	13463-67-7	
CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS		

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical Name Ethylene glycol CAS-No. 107-21-1

16. Other Information									
Revision Date: 10/28/2021				Supersedes Date:		New SDS			
Reason for revision: No Information									
Datasheet produced by: Regulatory Department			ent						
HMIS Ratir	ngs:								
Health:	1	Flammability:	2	Physical Hazard:	0	Personal Protection:	Х		
NFPA Ratings:									
Health:	1	Flammability:	2	Instability:	0	Physical & Chemical:			
Health: NFPA Rati	1								

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.