



# TUFFCOAT

## Cleaner & Degreaser

**CONCENTRATED COMMERCIAL STRENGTH  
FORMULA SAFELY & EASILY REMOVES:**

- **Grease, Grime, Wax & Oil**
- **Tree Sap**
- **Oxidation**
- **Food, Drink and Mildew Stains**

**USE ON CONCRETE, WOOD, FIBERGLASS, METALS AND PREVIOUSLY PAINTED SURFACES.**

**WATER-BASED, BIODEGRADABLE  
CONCENTRATED COMMERCIAL  
STRENGTH CLEANER AND DEGREASER**

### TECHNICAL INFORMATION

Tuff Coat Cleaner and Degreaser UT-15 contains a proprietary blend of biodegradable surfactants, detergents and emulsifiers in a water-based solution.

CONCENTRATED COMMERCIAL STRENGTH FORMULA EASILY REMOVES BUT NOT LIMITED TO THE FOLLOWING:

Food & Drink Stains  
Dried Latex Paint Spills  
Tape Residue  
Glue and Adhesive  
Acid Rain  
Bird Droppings  
Tree Sap  
Grease & Oil  
Marker and Crayon  
Scuff Marks  
Suntan Oil  
Tar and Wax  
Chewing Gum  
Mildew Stains

**COMPONENTS:** 1

**COVERAGE:**

Full Strength (Heavy Soils) – 250-300 sq. ft.

Reduced Strength 10:1 Water/Cleaner (Medium Soils) – 2,200 – 3,300 sq. ft.

Reduced Strength 30:1 Water/Cleaner (Light Soils) – 6,500 – 9,000 sq. ft.

**VOC:** 0%

**PH:** <12.2

**FLASH POINT:** Non-Flammable

**PACKAGED:** Gallon

**APPLICATION METHOD:** Cleaning rag, brush, pour or pressure washer.

**This product doesn't contain petroleum solvents, bleach or ammonia.**

**In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention.**

**KEEP OUT OF REACH OF CHILDREN.**

# TUFFCOAT



**APPLICATION INFORMATION:** This product is recommended for wood, concrete, metals, fiberglass and previously coated surfaces to clean prior to the use of Tuff Coat primers.

Shake thoroughly before use.

Always test on an inconspicuous area first. Apply directly on surface to be cleaned and allow to penetrate briefly. Wipe off with a clean cloth or towel.

For older, more difficult jobs, apply a generous amount of cleaner and allow to stand for a few minutes before wiping dry. For extremely tough jobs such as the removal of old, dried latex paint, scrub with a brush or scouring pad and wipe off with a wet rag.

#### **PRESSURE WASHER APPLICATION**

Contains anti-corrosive agents to safeguard pressure washer parts (bleach can erode O-rings). Please be aware that water pressure alone may remove paint or highlight existing discoloration caused by sun exposure.

Rinse surrounding plants with water before and after application. Wet the surface to be cleaned prior to applying the product. Place detergent application siphon tube and screen filter directly into container. Open the meter valve (if applicable) for maximum product flow. For reservoir machines, pour product (full strength) into pressure washer. Spray at low pressure onto a wet surface. On vertical surfaces, always spray from the top down. Allow product to remain on the surface for 3 to 5 minutes to penetrate. Do not allow product to dry on surface. Remove siphon tube from solution and rinse surface with high-pressure spray thoroughly. Flush siphon tube with clean water prior to storage.

**Do not use on varnished surfaces. Do not mix this product with any other chemicals.**